

CAPACITY TRAYS	
Code Model	
Cooking type	Convection, combi and steam cooking
	Convection, combi and steam cooking with Fixed Time or Core Probe function
	Convection, combi and steam cooking with Fixed Time or Core Probe function (optional)
Temperature setting	ACT Technology (Advanced CLIMA Technology) with energy conservation thanks to the automatic climate regulation
	Temperature settable from 30° to 280°
Cooking mode	Manual cooking mode
	Programmed cooking mode
	Automatic cooking mode
Recipes memory	Data storage for the saving of 99 programs
	Pre uploaded YESRECIPES book divided into categories
	MYCOOKBOOK for saving programs into customizable folders
	Rapid display of free and in use positions
Cooking Phases	5 cooking phases per program
	10 cooking phases per program
Pre-heating	HOLD function at the end of the cooking with automatic or settable mode
	Manual or automatic pre-heating mode settable up to 280°C
	Manual or automatic pre-heating mode settable up to 300°C
Control	Manual controls
	Multi-function digital display
	Multi-function digital display with YesClima function
	5"HD touchscreen display
	7"HD touchscreen display
Peripheral devices	10"HD touchscreen display
	Multilingual display
	Click&Share function to save recipes with your cover images
	USB interface for data uploading and downloading
	Download of HACCP data
Modifications and display	Configuration for integrated WIFI Connection
	Possibility to modify cooking parameters during the cycle in operation
Special cycles	Instant display of set cooking parameters
	Instant display of the set-up cooking program
	Alarms display with autodiagnosis system
	Delta T special cooking cycle
	Time's Up special cycle for synchronized cooking
	Cook and Go special cycle for cooking different recipes at the same time
	Rapid cooking chamber cool-down special cycle
	Regeneration special cycle with core cooking probe
	Regeneration by Time special cycle
	Proofing special cycle
Steam generation	Special cycle time extension at the end of the cooking process
	Rapid cancellation of memorized recipes
	Automatic special cycle for limescale removal from the boiler
	Manual humidity supply function
Humidity extraction	Fast Steam Technology for immediate steam generation from 0% to 100%
	YesSteam technology for steam generation with high-efficiency boiler with regulation from 0% to 100%
Heat supply	Forced manual removal of humidity
	Programmable FCS technology (Fast Chimney System) for forced removal of humidity
Fans speed	Automatic SCS Technology (Smart Chimney System) for forced removal of humidity
	Mono-fan heat supply system
	Multi-fan heat supply system
Cooking chamber	Additional settable ventilation SOFT-BAKING (*)
	Settable ventilation speeds (3)
	Settable ventilation speeds (7)
Oven structure	Pulse speed
	Automatic inversion of fans rotation
	304 stainless steel molded cooking chamber
	316 stainless steel molded cooking chamber
	Ergonomic and lightweight handle compliant with HACCP standards
	304 stainless steel control panel structure
	Frontal structure with screwless system
	Simply-removable control panel
	Simply-approachable right side
	Simply-approachable motor compartment
	Integrated humidity collector aisle
	Single chimney
Door	Double chimney
	One-point core probe with external link to the cooking chamber
	Multi-point core probe with external link to the cooking chamber
	Integrated syphon
	Adjustable feet
	Stackable kit configuration
	Simply-removable rack holder
	Simply-removable tray holder
	Door opening with Soft Touch technology and Anti Black-Out system
	Reversible door opening R/L
Lighting	Double glass door of easy inspection with high thermic insulation thermic insulation
	Halogen inner lamps in the cooking chamber
Security	Cooling fan for components protection
	Safety fanstop when the door is open
Washing	Manual external shower
	Retractable shower
	Automatic washing system with monocomponent YesClean (4+1 cycles)
Gas	Loading detergent function for checking the washing system status
	Washing delay start program
	Monoproduct tank
Atmospheric burners with high-efficiency corrugated heat-exchangers	

ego 7T	ego 11T	mood 7T	mood 11t	mosaico 7t	mosaico 11t
YEOGN11-7D	YEOGN11-11D	YMDGN11-7D	YMDGN11-11D	YMSGN11-7M	YMSGN11-11M
				☐	☐
☐	☐	☐	☐		
☐	☐				
☐	☐	☐	☐	☐	☐
☐	☐	☐	☐		
☐	☐				
☐	☐	☐	☐		
☐	☐				
☐	☐	☐	☐		
☐	☐				
☐	☐			☐	☐
☐	☐				
☐	☐	☐	☐		
☐	☐				
☐	☐				
☐	☐				
☐	☐				
☐	☐	☐	☐	☐	☐
☐	☐				
☐	☐				
☐	☐				
☐	☐				
☐	☐				
☐	☐				
☐	☐				
☐	☐				
☐	☐				
☐	☐	☐	☐	☐	☐
☐	☐				
☐	☐	☐	☐	☐	☐
☐	☐				
☐	☐				
☐	☐				
☐	☐				
☐	☐				
☐	☐				
☐	☐				
☐	☐				
☐	☐				
☐	☐	☐	☐	☐	☐
☐	☐				
☐	☐				
☐	☐				
☐	☐				
☐	☐				
☐	☐				
☐	☐				